

C Level Controller Type: Carbomat-M



Special features:

- Menu-guided operation
- Foil keyboard
- Exact C level control
- Soot limit monitoring
- Universal application of optional connection of O₂, O₂+CO₂, CO detectors and two thermocouples (type S or K)
- O₂ -probe monitoring (checking Ri and EMF, purging)
- Simultaneous measurement with two probes for super version
- Automatic change to spare probe
- Program memory with 99 set point programs for C level and temperature
- Analog output, for example, for recorder connection
- C level correction (for example, by means of foil specimens)
- Options:
 - Serial interface for example, for process visualized software "MESAVis"

Function:

The **Carbomat-M** is a single-channel measuring and control system for C level calculation and control in the furnace atmosphere of heat treatment plants.

By means of switch settings on the rear panel of the instrument, **Carbomat-M** can be easily adapted to match existing facilities. Alterations in the data acquisition scheme, for example, change of gas analyzers to oxygen probes, can be effected without difficulty.

A currently available analytical method for determining the carbon content in furnace atmospheres is the indirect measurement of the oxygen content in the furnace with zirconium oxide probes. **Carbomat-M** provides special support for these methods. Datasheets on probes and other equipment are available on request.

C Level Controller Type: Carbomat-M



Technical Data:

Construction:

Metal housing for mounting in control panels, in conformance with DIN 40050
Type of protection IP 54, as specified in DIN50050

Dimensions:

144 x 144 x 300 mm (l x w x h)

Auxiliary voltage:

230 Vac \pm 10 % 50/60 Hz

Power consumption:

About 15 VA

Input signals (selected by means of switch setting):

Analog (in following combinations):

- O₂ measuring probe, cell voltage directly or through amplifier
- O₂ measuring probe and CO analyzer
- CO₂ analyzer
- CO₂ analyzer and CO analyzer
- O₂ probe and L-probe
- O₂ probe, L-probe and CO analyzer
- L - probe and CO analyzer
- L - probe and CO₂ analyzer
- L- probe, CO₂ analyzer and CO analyzer
- L- probe and L-probe
- O₂ probe and O₂ probe
- CO analyzer and O₂ probe

Attention:

If you use L-probe and O₂ - probe you can't connect an additional Reference junction.

- Thermocouple, type K or S
- Reference junction, type K or S (also mixed)
- Terminal temperature (Pt 100)
- External set value: analog or through **serial interface**

Digital:

- IN 0: program release with set point program in progress: otherwise, controller locked
- IN 1: program continuation in succession
- IN 2: input disable

Serial interface(option):

- RS 232
- RS 422 / RS 485
- 20 mA current loop (TTY)

Output signals:

Analog:

- C potential actual value, selected, 0 to 20 mA, 4 to 20 mA or 0 to 10 Vdc
(in three scale divisions: 0...1,5 %; 0,15...1,5 %; 0...2,0 %)

Option: -Integrated temperature transmitter - 11 additional control tracks with an external box.

Switching outputs:

- 5 control tracks freely available
- 2 switching outputs for 1 motor valve for gas or solenoid valves for gas and air
- Signal gas release
- Signal probe purging
- Signal actual values in tolerance range
- Signal program active
- Signal Alarm indication

(all outputs "open collector" 24 V / 100 mA)

Display:

Graphical LCD display with 160 x 128 pixels

Operation:

Five keys (soft keys) with user guidance (menu guidance);
respective function of the keys indicated on display

Set point:

- 4 preset points for C level
- 99 set point programs for C level profiles, internally storable and recallable;
(program travel time per program: up to 100 h)
- 23 segments / program
- External entry by means of program generator, for example, 0...20 mA, 4...20 mA, 0...10 V.

Option:

- 99 set point programs for C level and temperature profiles
- Set point through serial interface

Climate:

Storage: -10...+60 °C
Operation: 0...+50 °C
5...95 % relative humidity, non-condensing
Impedance for cell voltage: > 100 MOhm